



**THERMISCHE EIGENSCHAPPEN**

Operat. temp. vast min./max. [°C]	-50 °C / +90 °C
Operat. temp. bewegend min/max [°C]	-40 °C / +90 °C

**EIGENSCHAPPEN IN GEVAL VAN BRAND**

Brandgedrag	volgens IEC 60332-1, vlamtest van kabel, FT1
-------------	--

**STANDAARDS & GOEDKEURINGEN**

Goedkeuringen	UL/CSA - cURus 80 °C, 1.000 V
---------------	-------------------------------

**ARTIKELOVERZICHT****KAWEFLEX Allround 7320 SK-TPE UL/CSA**

Artikelnr. [JOBARCO]	Afmeting	Buiten-Ø [mm]	Cu Index [kg/km]	Gewicht [kg/km]
T1705203	4 G 1,5 (AWG 16)	7,6	58,0	97,0
T1705213	4 G 2,5 (AWG 14)	9,0	96,0	151,0
	5 G 2,5 (AWG 14)	9,8	120,0	187,0
T1705224	4 G 4 (AWG 12)	10,9	158,0	232,0
T1705225	5 G 4 (AWG 12)	12,1	192,0	295,0
	4 X 6 (AWG 10)	13,4	231,0	348,0
T1705234	4 G 6 (AWG 10)	13,4	231,0	348,0
T1705235	5 G 6 (AWG 10)	15,0	288,0	436,0
T1705245	4 G 10 (AWG 8)	17,2	384,0	570,0
T1705246	5 G 10 (AWG 8)	19,3	480,0	721,0
T1705256	4 G 16 (AWG 6)	20,4	614,0	849,0
T1705257	5 G 16 (AWG 6)	23,0	768,0	1.056,0
T1705267	4 G 25 (AWG 4)	24,5	960,0	1.206,0
T1705277	4 G 35 (AWG 2)	31,0	1.344,0	1.914,0
T1705287	4 G 50 (AWG 1)	36,6	1.920,0	2.715,0
	4 G 70 (AWG 2/0)	38,8	2.688,0	3.450,0