



**THERMISCHE EIGENSCHAPPEN**

Operat. temp. vast min./max. [°C]	-50 °C / +90 °C
Operat. temp. bewegend min/max [°C]	-40 °C / +90 °C

**EIGENSCHAPPEN IN GEVAL VAN BRAND**

Brandgedrag	volgens IEC 60332-1, vlamtest van kabel, FT1
-------------	--

**STANDAARDS & GOEDKEURINGEN**

Goedkeuringen	UL/CSA - cURus 80°C, 1000 V
---------------	-----------------------------

**ARTIKELOVERZICHT****KAWEFLEX Allround 7420 SK-C-TPE UL/CSA**

Artikelnr. [JOBARCO]	Afmeting	Buiten-Ø [mm]	Cu Index [kg/km]	Gewicht [kg/km]
T1705823	4 G 1,5 (AWG 16)	9,8	86,0	148,0
T1705833	4 G 2,5 (AWG 14)	11,2	132,0	210,0
	5 G 2,5 (AWG 14)	12,4	150,0	260,0
T1705843	4 G 4 (AWG 12)	13,7	212,0	325,0
T1705844	5 G 4 (AWG 12)	14,9	260,0	395,0
T1705853	4 G 6 (AWG 10)	16,2	305,0	461,0
T1705854	5 G 6 (AWG 10)	17,8	378,0	561,0
T1705863	4 G 10 (AWG 8)	19,9	513,0	692,0
	5 G 10 (AWG 8)	22,5	660,0	920,0
T1705873	4 G 16 (AWG 6)	22,5	805,0	1.093,0
T1705874	5 G 16 (AWG 6)	27,9	990,0	1.405,0
T1705883	4 G 25 (AWG 4)	27,6	1.147,0	1.473,0
T1705892	4 G 35 (AWG 2)	34,6	1.650,0	2.290,0
T1705901	4 G 50 (AWG 1)	40,4	2.300,0	3.240,0